

20AOF16C500KR

20-bit, 16 channel, 500K S/S/Ch Analog Output

CPCI6U64-20AOF16C500KR

Linux Device Driver And API Library User Manual

**Manual Revision: April 21, 2023
Driver Release Version 2.6.102.45.1**

**General Standards Corporation
8302A Whitesburg Drive
Huntsville, AL 35802
Phone: (256) 880-8787
Fax: (256) 880-8788**

URL: <http://www.generalstandards.com>

E-mail: sales@generalstandards.com

E-mail: support@generalstandards.com

Preface

Copyright © 2011-2023, **General Standards Corporation**

Additional copies of this manual or other literature may be obtained from:

General Standards Corporation
8302A Whitesburg Dr.
Huntsville, Alabama 35802
Phone: (256) 880-8787
FAX: (256) 880-8788
URL: <http://www.generalstandards.com>
E-mail: sales@generalstandards.com

General Standards Corporation makes no warranty of any kind with regard to this documentation and/or software, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Although extensive editing and reviews are performed before release, **General Standards Corporation** assumes no responsibility for any errors, inaccuracies or omissions herein. This documentation, information and software are made available solely on an “as-is” basis. Nor is there any commitment to update or keep current this documentation.

General Standards Corporation does not assume any liability arising out of the application or use of documentation, software, product or circuit described herein, nor is any license conveyed under any patent rights or any rights of others.

General Standards Corporation assumes no responsibility for any consequences resulting from omissions or errors in this manual or from the use of information contained herein.

General Standards Corporation reserves the right to make any changes, without notice, to this documentation, software or product, to improve accuracy, clarity, reliability, performance, function, or design.

ALL RIGHTS RESERVED.

GSC is a trademark of **General Standards Corporation**.

PLX and PLX Technology are trademarks of PLX Technology, Inc.

Table of Contents

1. Introduction.....	8
1.1. Purpose.....	8
1.2. Acronyms.....	8
1.3. Definitions	8
1.4. Software Overview	8
1.4.1. Basic Software Architecture	8
1.4.2. API Library.....	9
1.4.3. Device Driver	9
1.5. Hardware Overview	9
1.6. Reference Material.....	9
1.7. Licensing.....	10
2. Installation.....	11
2.1. CPU and Kernel Support.....	11
2.1.1. 32-bit Support Under 64-bit Environments	12
2.2. The /proc/ File System	12
2.3. File List.....	12
2.4. Directory Structure.....	12
2.5. Installation	13
2.6. Removal.....	13
2.7. Overall Make Script.....	13
2.8. Environment Variables	14
2.8.1. GSC_API_COMP_FLAGS.....	14
2.8.2. GSC_API_LINK_FLAGS.....	14
2.8.3. GSC_LIB_COMP_FLAGS.....	14
2.8.4. GSC_LIB_LINK_FLAGS.....	15
2.8.5. GSC_APP_COMP_FLAGS.....	15
2.8.6. GSC_APP_LINK_FLAGS.....	15
3. Main Interface Files.....	16
3.1. Main Header File	16
3.2. Main Library File.....	16
3.2.1. Build	16
3.2.2. System Libraries.....	17
4. API Library	18
4.1. Files.....	18
4.2. Build	18
4.3. Library Use	18
4.4. Macros	19
4.4.1. IOCTL Services.....	19

4.4.2. Registers	19
4.5. Data Types	19
4.6. Functions.....	19
4.6.1. aof16c500kr_close()	20
4.6.2. aof16c500kr_init()	20
4.6.3. aof16c500kr_ioctl()	21
4.6.4. aof16c500kr_open()	22
4.6.5. aof16c500kr_read()	23
4.6.6. aof16c500kr_write()	24
4.7. IOCTL Services	25
4.7.1. AOF16C500KR_IOCTL_AUTO_CALIBRATE	25
4.7.2. AOF16C500KR_IOCTL_AUTO_CAL_STS	25
4.7.3. AOF16C500KR_IOCTL_BUF_CLEAR	25
4.7.4. AOF16C500KR_IOCTL_BUF_MODE	25
4.7.5. AOF16C500KR_IOCTL_BUF_OVER_DATA	26
4.7.6. AOF16C500KR_IOCTL_BUF_OVER_FRAME	26
4.7.7. AOF16C500KR_IOCTL_BUF_SIZE	27
4.7.8. AOF16C500KR_IOCTL_BUF_THRESH	27
4.7.9. AOF16C500KR_IOCTL_BUF_THR_STS	27
4.7.10. AOF16C500KR_IOCTL_BURST_ENABLE	27
4.7.11. AOF16C500KR_IOCTL_BURST_READY	28
4.7.12. AOF16C500KR_IOCTL_BURST_TRIG_SRC	28
4.7.13. AOF16C500KR_IOCTL_CHANNEL_SEL	28
4.7.14. AOF16C500KR_IOCTL_CLOCK_ENABLE	29
4.7.15. AOF16C500KR_IOCTL_CLOCK_READY	29
4.7.16. AOF16C500KR_IOCTL_CLOCK_SRC	29
4.7.17. AOF16C500KR_IOCTL_CLOCK_SW	30
4.7.18. AOF16C500KR_IOCTL_DATA_FORMAT	30
4.7.19. AOF16C500KR_IOCTL_DIO_DIR_OUT	30
4.7.20. AOF16C500KR_IOCTL_DIO_READ	30
4.7.21. AOF16C500KR_IOCTL_DIO_WRITE	31
4.7.22. AOF16C500KR_IOCTL_FILTER	31
4.7.23. AOF16C500KR_IOCTL_GEN_A_ENABLE	31
4.7.24. AOF16C500KR_IOCTL_GEN_A_NDIV	32
4.7.25. AOF16C500KR_IOCTL_GEN_B_ENABLE	32
4.7.26. AOF16C500KR_IOCTL_GEN_B_NDIV	32
4.7.27. AOF16C500KR_IOCTL_GROUND_SENSE	32
4.7.28. AOF16C500KR_IOCTL_INITIALIZE	33
4.7.29. AOF16C500KR_IOCTL_IRQ_SEL	33
4.7.30. AOF16C500KR_IOCTL_LED	34
4.7.31. AOF16C500KR_IOCTL_LOAD_READY	34
4.7.32. AOF16C500KR_IOCTL_LOAD_REQUEST	34
4.7.33. AOF16C500KR_IOCTL_OUTPUT_MODE	34
4.7.34. AOF16C500KR_IOCTL_QUERY	35
4.7.35. AOF16C500KR_IOCTL_RANGE	36
4.7.36. AOF16C500KR_IOCTL_REG_MOD	36
4.7.37. AOF16C500KR_IOCTL_REG_READ	37
4.7.38. AOF16C500KR_IOCTL_REG_WRITE	37
4.7.39. AOF16C500KR_IOCTL_TRIGGER_SW	38
4.7.40. AOF16C500KR_IOCTL_TX_IO_ABORT	38
4.7.41. AOF16C500KR_IOCTL_TX_IO_MODE	38
4.7.42. AOF16C500KR_IOCTL_TX_IO_OVR_DAT	39
4.7.43. AOF16C500KR_IOCTL_TX_IO_OVR_FRM	39
4.7.44. AOF16C500KR_IOCTL_TX_IO_TIMEOUT	39

4.7.45. AOF16C500KR_IOCTL_WAIT_CANCEL	40
4.7.46. AOF16C500KR_IOCTL_WAIT_EVENT	40
4.7.47. AOF16C500KR_IOCTL_WAIT_STATUS	42
4.7.48. AOF16C500KR_IOCTL_XCVR_OUTPUT	43
4.7.49. AOF16C500KR_IOCTL_XCVR_POL	43
4.7.50. AOF16C500KR_IOCTL_XCVR_TYPE	44
5. The Driver.....	45
5.1. Files.....	45
5.2. Build	45
5.3. Startup.....	45
5.3.1. Manual Driver Startup Procedures	45
5.3.2. Automatic Driver Startup Procedures.....	46
5.4. Verification	47
5.5. Version.....	48
5.6. Shutdown	48
6. Document Source Code Examples.....	49
6.1. Files.....	49
6.2. Build	49
6.3. Library Use	49
7. Utility Source Code.....	50
7.1. Files.....	50
7.2. Build	50
7.3. Library Use	50
8. Operating Information	51
8.1. Debugging Aids	51
8.1.1. Device Identification	51
8.1.2. Detailed Register Dump	51
8.2. Analog Output Configuration	51
8.3. I/O Modes	51
8.3.1. PIO - Programmed I/O	52
8.3.2. BMDMA - Block Mode DMA	52
8.3.3. DMDMA - Demand Mode DMA	52
9. Sample Applications	53
9.1. aout - Analog Output - ../aout/	53
9.2. din - Digital Input - ../din/	53
9.3. dout - Digital Output - ../dout/	53
9.4. fsamp - Sample Rate - ../fsamp/	53
9.5. id - Identify Board - ../id/	53
9.6. irq - Interrupt Test - ../irq/	53

9.7. led – LED Exerciser - .../led/	53
9.8. regs - Register Access - .../regs/	53
9.9. signals - Digital Signals - .../signals/	53
9.10. txrate – Transmit Rate - .../txrate/	54
Document History	55

Table of Figures

Figure 1 Architectural representation.9

1. Introduction

1.1. Purpose

The purpose of this document is to describe the interface to the 20AOF16C500KR API Library and to the underlying Linux device driver. The API Library software provides the interface between "Application Software" and the device driver. The driver software provides the interface between the API Library and the actual 20AOF16C500KR hardware. The API Library and driver interfaces are based on the board's functionality.

1.2. Acronyms

The following is a list of commonly occurring acronyms which may appear throughout this document.

Acronyms	Description
API	Application Programming Interface
BMDMA	Block Mode DMA
DAC	Digital to Analog Converter
DIO	Digital I/O
DMA	Direct Memory Access
DMDMA	Demand Mode DMA
GSC	General Standards Corporation
cPCI	Compact PCI
PCI	Peripheral Component Interconnect
PIO	Programmed I/O

1.3. Definitions

The following is a list of commonly occurring terms which may appear throughout this document.

Term	Definition
...	This is a shortcut representation of the 20AOF16C500KR installation directory or any of its subdirectories.
20AOF16C500KR	This is used as a general reference to any board supported by this driver.
API Library	This is a library that provides application-level access to 20AOF16C500KR hardware.
Application	This is a user mode process, which runs in user space with user mode privileges.
Driver	This is the 20AOF16C500KR device driver, which runs in kernel space with kernel mode privileges.
Library	This is usually a general reference to the API Library.

1.4. Software Overview

1.4.1. Basic Software Architecture

This section describes the general architecture for the basic components that comprise 20AOF16C500KR applications. The overall architecture is illustrated in Figure 1 below.




Figure 1 Architectural representation.

1.4.2. API Library

The primary means of accessing 20AOF16C500KR boards is via the 20AOF16C500KR API Library. This library forms a thin layer between the application and the driver. Additional information is given in section 4 beginning on page 18. With the library, applications are able to open and close a device and, while open, perform I/O control and write operations.

1.4.3. Device Driver

The device driver is the host software that provides a means of communicating directly with 20AOF16C500KR hardware. The driver executes under control of the operating system and runs in Kernel Mode as a Kernel Mode device driver. The driver is implemented as a standard dynamically loadable Linux device driver written in the C programming language. While applications can access the driver directly without use of the API Library, it is recommended that all access is made through the library.

1.5. Hardware Overview

The 20AOF16C500KR is a high-performance, 20-bit analog output board that incorporates 16, 12, 8 or 4 output channels. The host side connection is PCI based and the form factor is according to the model ordered. The board is capable of outputting data at up to 500K samples per second over each channel. Internal clocking permits sampling rates from 500K samples per second down to 3 samples per second. Onboard storage permits data buffering of up to 256K samples, for all channels collectively, between the PCI bus and the cable interface. This allows the 20AOF16C500KR to sustain continuous throughput to the cable interface independent of the PCI bus interface. The 20AOF16C500KR also permits multiple boards to be synchronized so that all boards output data in unison. The board also incorporates eight bidirectional digital I/O lines.

1.6. Reference Material

The following reference material may be of particular benefit in using the 20AOF16C500KR. The specifications provide the information necessary for an in depth understanding of the specialized features implemented on this board.

- The applicable *20AOF16C500KR User Manual* from General Standards Corporation.
- The *PCI9656 PCI Bus Master Interface Chip* data handbook from PLX Technology, Inc.

PLX Technology Inc.
870 Maude Avenue
Sunnyvale, California 94085 USA
Phone: 1-800-759-3735
WEB: <http://www.plxtech.com>

1.7. Licensing

For licensing information please refer to the text file `LICENSE.txt` in the root installation directory.

2. Installation

2.1. CPU and Kernel Support

The driver is designed to operate with Linux kernel versions 6.x, 5.x, 4.x, 3.x, 2.6, 2.4 and 2.2 running on a PC system with one or more x86 processors. This release of the driver supports the below listed kernels.

Kernel	Distribution
6.0.7	Red Hat Fedora Core 37
5.17.5	Red Hat Fedora Core 36
5.14.10	Red Hat Fedora Core 35
5.11.12	Red Hat Fedora Core 34
5.8.15	Red Hat Fedora Core 33
5.6.6	Red Hat Fedora Core 32
5.3.7	Red Hat Fedora Core 31
5.0.9	Red Hat Fedora Core 30
4.18.16	Red Hat Fedora Core 29
4.16.3	Red Hat Fedora Core 28
4.13.9	Red Hat Fedora Core 27
4.11.8	Red Hat Fedora Core 26
4.8.6	Red Hat Fedora Core 25
4.5.5	Red Hat Fedora Core 24
4.2.3	Red Hat Fedora Core 23
4.0.4	Red Hat Fedora Core 22
3.17.4	Red Hat Fedora Core 21
3.11.10	Red Hat Fedora Core 20
3.9.5	Red Hat Fedora Core 19
3.6.10	Red Hat Fedora Core 18
3.3.4	Red Hat Fedora Core 17
3.1.0	Red Hat Fedora Core 16
2.6.38	Red Hat Fedora Core 15
2.6.35	Red Hat Fedora Core 14
2.6.33	Red Hat Fedora Core 13
2.6.31	Red Hat Fedora Core 12
2.6.29	Red Hat Fedora Core 11
2.6.27	Red Hat Fedora Core 10
2.6.25	Red Hat Fedora Core 9
2.6.23	Red Hat Fedora Core 8
2.6.21	Red Hat Fedora Core 7
2.6.18	Red Hat Fedora Core 6
2.6.15	Red Hat Fedora Core 5
2.6.11	Red Hat Fedora Core 4
2.6.9	Red Hat Fedora Core 3

NOTE: Some older kernel versions are supported (the sources are maintained), but are not tested.

NOTE: While only Red Hat Fedora distributions are listed, numerous other distributions are supported and have been tested on an as needed basis.

NOTE: The driver will have to be built before being used as it is provided in source form only.

NOTE: The driver has not been tested with a non-versioned kernel.

NOTE: The driver has not been tested for SMP operation.

2.1.1. 32-bit Support Under 64-bit Environments

This driver supports 32-bit applications under 64-bit environments. The availability of this feature in the kernel depends on a 64-bit kernel being configured to support 32-bit application compatibility. Additionally, 2.6 kernels prior to 2.6.11 implemented 32-bit compatibility in a way that resulted in some drivers not being able to take advantage of the feature. (In these kernels a driver's IOCTL command codes must be globally unique. Beginning with 2.6.11 this requirement has been lifted.) If the driver is not able to provide 32-bit support under a 64-bit kernel, the "32-bit support" field in the `/proc/20aof16c500kr` file will be "no".

2.2. The `/proc/` File System

While the driver is running, the text file `/proc/20aof16c500kr` can be read to obtain information about the driver. Each file entry includes an entry name followed immediately by a colon, a space character, and the entry value. Below is an example of what appears in the file, followed by descriptions of each entry.

```
version: 2.6.102.45
32-bit support: yes
boards: 1
models: 20AOF16C500KR
```

Entry	Description
version	This gives the driver version number in the form <code>x.x.x.x</code> .
32-bit support	This reports the driver's support for 32-bit applications. This will be either "yes" or "no" for 64-bit driver builds and "yes (native)" for 32-bit builds.
boards	This identifies the total number of boards the driver detected.
models	This gives a comma separated list of the board models identified by the driver. One model will be listed for each board identified in the system. For this driver the only model numbers listed will be "20AOF16C500KR."

2.3. File List

This release consists of the below listed primary files. The archive is described in detail in the following subsections.

File	Description
<code>20aof16c500kr.linux.tar.gz</code>	This archive contains the driver, the API Library and all related files.
<code>20aof16c500kr_linux_um.pdf</code>	This is a PDF version of this user manual, which is included in the archive.

2.4. Directory Structure

The following table describes the directory structure utilized by the installed files. During installation the directory structure is created and populated with the respective files.

Directory	Content
<code>20aof16c500kr/</code>	This is the driver root directory. It contains the documentation, the Overall Make Script (section 2.7, page 13) and the below listed subdirectories.
<code>.../api/</code>	This directory contains the 20AOF16C500KR API Library (section 4, page 18).
<code>.../docsrc/</code>	This directory contains the code samples from this document (section 6 on page 49).
<code>.../driver/</code>	This directory contains the driver and its sources (section 5, page 45).
<code>.../include/</code>	This directory contains the include files for the various libraries.

.../lib/	This directory contains all of the libraries built from the driver archive.
.../samples/	This directory contains the sample applications (section 9, page 53).
.../utils/	This directory contains utility sources used by the sample applications (section 7, page 50).

2.5. Installation

Perform installation following the below listed steps. This installs the device driver, the API Library and all related sources and documentation.

1. Create and change to the directory where the files are to be installed, such as `/usr/src/linux/drivers/`. (The path name may vary among distributions and kernel versions.)
2. Copy the archive file `20aof16c500kr.linux.tar.gz` into the current directory.
3. Issue the following command to decompress and extract the files from the provided archive. This creates the directory `20aof16c500kr` in the current directory, and then copies all of the archive's files into this new directory.

```
tar -xzvf 20aof16c500kr.linux.tar.gz
```

2.6. Removal

Perform removal following the below listed steps. This removes the device driver, the API Library and all related sources and documentation.

NOTE: The following steps may require elevated privileges.

1. Shutdown the driver as described in section 5.6 on page 48.
2. Change to the directory where the driver archive was installed, which may have been `/usr/src/linux/drivers/`. (The path name may vary among distributions and kernel versions.)
3. Issue the below command to remove the driver archive and all of the installed driver files.

```
rm -rf 20aof16c500kr.linux.tar.gz 20aof16c500kr
```

4. Issue the below command to remove all of the installed device nodes.

```
rm -f /dev/20aof16c500kr.*
```

5. If the automated startup procedure was adopted (section 5.3.2, page 46), then edit the system startup script `rc.local` and remove the line that invokes the 20AOF16C500KR's `start` script. The file `rc.local` should be located in the `/etc/rc.d/` directory.

2.7. Overall Make Script

An Overall Make Script is included in the root installation directory. Executing this script will perform a make for all build targets included in the release. The script also loads the driver and copies the API Library to `/usr/lib/`. The script is named `make_all`. Follow the below steps to perform an overall make and to load the driver.

NOTE: The following steps may require elevated privileges.

1. Change to the driver root directory (`.../20aof16c500kr/`).

- Issue the following command to remove all archive build targets.

```
./make_all clean
```

- Issue the following command to make all archive targets and to load the driver.

```
./make_all
```

NOTE: After the device driver is built the script starts the driver. After building the API Library it is copied by the script to `/usr/lib/`. The script can also perform a clean operation by adding the term “clean” as a command line argument. A clean operation does not unload the driver. However, a clean does delete the API Library file copied to `/usr/lib/`.

2.8. Environment Variables

Some build environments may require compiler or linker options not present in the provided make files. To accommodate local environment specific requirements, the provided make files incorporate support for the following set of GSC specific environment variables.

2.8.1. GSC_API_COMP_FLAGS

This environment variable accommodates adding compiler command line options when compiling source files for the API Library. The compiler used by the API Library make file is “gcc”. The content of this environment variable is noted in the make file’s output to the screen. The table below shows a portion of the screen output. The “xxx” in the table refers to the contents of the environment variable. This environment variable has no effect on compiling any other distributed source files or linking of any object files.

Undefined or Empty	== Compiling: init.c == Compiling: ioctl.c == Compiling: open.c
Defined and Not Empty	== Compiling: init.c (added 'xxx') == Compiling: ioctl.c (added 'xxx') == Compiling: open.c (added 'xxx')

2.8.2. GSC_API_LINK_FLAGS

This environment variable accommodates adding linker command line options when linking object files for the API Library. The linker used by the API Library make file is “ld”. The content of this environment variable is noted in the make file’s output to the screen. The table below shows a portion of the screen output. The “xxx” in the table refers to the contents of the environment variable. This environment variable has no effect on compiling of any source files or linking of any other object files.

Undefined or Empty	==== Linking: ../lib/lib20aof16c500kr_api.so
Defined and Not Empty	==== Linking: ../lib/lib20aof16c500kr_api.so (added 'xxx')

2.8.3. GSC_LIB_COMP_FLAGS

This environment variable accommodates adding compiler command line options when compiling source files for the utility libraries. The compiler used by the utility library make files is “gcc”. The content of this environment variable is noted in the make files’ output to the screen. The table below shows a portion of the screen output. The

“xxx” in the table refers to the contents of the environment variable. This environment variable has no effect on compiling any other distributed source files or linking of any object files.

Undefined or Empty	== Compiling: close.c == Compiling: init.c == Compiling: ioctl.c
Defined and Not Empty	== Compiling: close.c (added 'xxx') == Compiling: init.c (added 'xxx') == Compiling: ioctl.c (added 'xxx')

2.8.4. GSC_LIB_LINK_FLAGS

This environment variable accommodates adding linker command line options when linking object files for the utility libraries. The linker used by the utility library make files is “ld”. The content of this environment variable is noted in the make files’ output to the screen. The table below shows a portion of the screen output. The “xxx” in the table refers to the contents of the environment variable. This environment variable has no effect on compiling of any source files or linking of any other object files.

Undefined or Empty	==== Linking: ../lib/20aof16c500kr_utils.a
Defined and Not Empty	==== Linking: ../lib/20aof16c500kr_utils.a (added 'xxx')

2.8.5. GSC_APP_COMP_FLAGS

This environment variable accommodates adding compiler command line options when compiling source files for the sample applications. The compiler used by the sample application make files is “gcc”. The content of this environment variable is noted in the make files’ output to the screen. The table below shows a portion of the screen output. The “xxx” in the table refers to the contents of the environment variable. This environment variable has no effect on compiling any other distributed source files or linking of any object files.

Undefined or Empty	== Compiling: main.c == Compiling: perform.c
Defined and Not Empty	== Compiling: main.c (added 'xxx') == Compiling: perform.c (added 'xxx')

2.8.6. GSC_APP_LINK_FLAGS

This environment variable accommodates adding linker command line options when linking object files for the sample applications. The linker used by the sample application make files is “gcc”. The content of this environment variable is noted in the make files’ output to the screen. The table below shows a portion of the screen output. The “xxx” in the table refers to the contents of the environment variable. This environment variable has no effect on compiling of any source files or linking of any other object files.

Undefined or Empty	==== Linking: id
Defined and Not Empty	==== Linking: id (added 'xxx')

3. Main Interface Files

This section gives general information on the suggested device interface files to use when developing 20AOF16C500KR based applications.

3.1. Main Header File

Throughout the remainder of this document references are made to various header files included as part of the 20AOF16C500KR driver archive. For ease of use it is suggested that applications include only the single header file shown below rather than individually including those headers identified separately later in this document. Including this header file pulls in all other pertinent 20AOF16C500KR specific header files. Therefore, sources may include only this one 20AOF16C500KR header and make files may reference only this one 20AOF16C500KR include directory.

Description	File	Location
Header File	20aof16c500kr_main.h	.../include/

3.2. Main Library File

Throughout the remainder of this document references are made to various statically linkable libraries included as part of the 20AOF16C500KR driver archive. For ease of use it is suggested that applications link only the single library file shown below rather than individually linking those libraries identified separately later in this document. Linking this library file pulls in all other pertinent 20AOF16C500KR specific static libraries. Therefore, make files may reference only this one 20AOF16C500KR static library and only this one 20AOF16C500KR library directory.

Description	File	Location
Static Library	20aof16c500kr_main.a	.../lib/
	20aof16c500kr_multi.a	

NOTE: For applications using the 20AOF16C500KR and no other GSC devices, link the 20aof16c500kr_main.a library. For applications using multiple GSC device types, link the xxxx_main.a library for one of the devices and the xxxx_multi.a library for the others. Linking multiple xxxx_main.a libraries may likely produce link errors due to duplicate symbols being defined. While it may make little or no difference, it is recommended that one choose the xxxx_main.a library from the driver with the largest number in positions three (x.x.X.x.x) and/or four (x.x.x.X.x) in the driver release version number.

NOTE: The 20AOF16C500KR API Library is implemented as a shared library and is thus not linked with the 20AOF16C500KR Main Library. The API Library must be linked with applications by adding the argument `-l20aof16c500kr_api` to the linker command line.

3.2.1. Build

The main library is built via the Overall Make Script (section 2.7, page 13). However, the main library can be rebuilt separately following the below steps.

1. Change to the directory where the main library resides (.../lib/).
2. Remove existing build targets using the below command.

```
make clean
```
3. Rebuild the main library by issuing the below command.

make

3.2.2. System Libraries

In addition to linking the static library named above, applications may need to also link in additional system libraries as noted below.

Library	gcc Link Flag
Math	-lm
POSIX Thread	-lpthread
Real Time	-lrt

4. API Library

The 20AOF16C500KR API Library is the software interface between user applications and the 20AOF16C500KR device driver. The interface is accessed by including the header file `20aof16c500kr_api.h`.

NOTE: Contact General Standards Corporation if additional library functionality is required.

4.1. Files

The library files are summarized in the table below.

File	Description
<code>api/*.c</code>	These are library source files.
<code>api/*.h</code>	These are library header files.
<code>api/makefile</code>	This is the library make file.
<code>api/makefile.dep</code>	This is an automatically generated make dependency file.
<code>include/20aof16c500kr_api.h</code>	This is the library interface header file.
<code>lib/lib20aof16c500kr_api.so</code>	This is the API Library shared library file. *

* The shared library is automatically copied to `/usr/lib/` when it is built.

4.2. Build

The API Library is built via the Overall Make Script (section 2.7, page 13), but can be built separately following the below steps.

NOTE: The API Library shared library is copied to `/usr/lib/`. Therefore, these steps may require elevated privileges.

1. Change to the directory where the library sources are installed (`.../api/`).
2. Remove existing build targets using the below command.

```
make clean
```

3. Compile the source files and build the library by issuing the below command.

```
make
```

4.3. Library Use

The library is used at application compile time, at application link time and at application run time. At compile time include the below listed header file in each source file using a component of the library interface. At link time include the below listed linker argument on the linker command line. At link time and at run time the library is found in the directory `/usr/lib/`. (The shared library file is automatically copied to `/usr/lib/` when the library is built.)

Description	File	Location	Linker Argument
Header File	<code>20aof16c500kr_api.h</code>	<code>.../include/</code>	
Shared Library	<code>lib20aof16c500kr_api.so</code>	<code>.../lib/</code> <code>/usr/lib/</code>	<code>-l20aof16c500kr_api</code>

4.4. Macros

The API Library and driver interfaces include the following macros, which are defined in `20aof16c500kr.h`.

4.4.1. IOCTL Services

The IOCTL macros are documented in section 4.7 beginning on page 25.

4.4.2. Registers

The following gives the complete set of 20AOF16C500KR registers.

4.4.2.1. GSC Registers

The following table gives the complete set of GSC specific 20AOF16C500KR registers. For detailed definitions of these registers refer to the relevant 20AOF16C500KR User Manual. Please note that the set of registers supported by any given board may vary according to model and firmware version. For the set of supported registers and detailed definitions of these registers please refer to the appropriate *20AOF16C500KR User Manual*.

Macro	Description
<code>AOF16C500KR_GSC_ACR</code>	Assembly Configuration Register (ACR)
<code>AOF16C500KR_GSC_AOBR</code>	Analog Output Buffer Register (AOBR)
<code>AOF16C500KR_GSC_AVR</code>	Auto Cal Values Register (AVR)
<code>AOF16C500KR_GSC_BCR</code>	Board Control Register (BCR)
<code>AOF16C500KR_GSC_BOOR</code>	Buffered Output Operations Register (BOOR)
<code>AOF16C500KR_GSC_DIOPR</code>	Digital I/O Port Register (DIOPR)
<code>AOF16C500KR_GSC_OBSR</code>	Output Buffer Size Register (OBSR)
<code>AOF16C500KR_GSC_OBTR</code>	Output Buffer Threshold Register (OBTR)
<code>AOF16C500KR_GSC_OCR</code>	Output Configuration Register (OCR)
<code>AOF16C500KR_GSC_PSR</code>	Primary Status Register (PSR)
<code>AOF16C500KR_GSC_RAGR</code>	Rate-A Generator Register (RAGR)
<code>AOF16C500KR_GSC_RBGR</code>	Rate-B Generator Register (RBGR)

4.4.2.2. PCI Configuration Registers

Access to the PCI registers is seldom required so these registers are not listed here. For the complete list of the PCI register identifiers refer to the driver header file `gsc_pci9656.h`, which is automatically included via `20aof16c500kr.h`.

4.4.2.3. PLX PCI9656 Feature Set Registers

Access to the PLX registers is seldom required so these registers are not listed here. For the complete list of the PLX register identifiers refer to the driver header file `gsc_pci9656.h`, which is automatically included via `20aof16c500kr.h`.

4.5. Data Types

The data types used by the API Library are described with the IOCTL services with which they are used.

4.6. Functions

The interface includes the following functions. The return values reflect the completion status of the requested operation. A value of zero indicates success. A negative value indicates that the request could not be completed.

successfully. The specific value returned is the negative of the corresponding error status value taken from `errno.h`. I/O services return positive values to indicate the number of bytes successfully transferred.

4.6.1. `aof16c500kr_close()`

This function is the entry point to close a connection to an open 20AOF16C500KR board. The board is put in an initialized state before this call returns.

Prototype

```
int aof16c500kr_close(int fd);
```

Argument	Description
fd	This is the file descriptor of the device to be closed.

Return Value	Description
0	The operation succeeded.
< 0	An error occurred. This is the negative of <code>errno</code> from <code>errno.h</code> .

Example

```
#include <stdio.h>

#include "20aof16c500kr_dsl.h"

int aof16c500kr_close_dsl(int fd)
{
    int errs;
    int ret;

    ret = aof16c500kr_close(fd);

    if (ret)
        printf("ERROR: aof16c500kr_close() returned %d\n", ret);

    errs = ret ? 1 : 0;
    return(errs);
}
```

4.6.2. `aof16c500kr_init()`

This function is the entry point to initializing the 20AOF16C500KR API Library and must be the first call into the Library. This function may be called more than once, but only the first successful call actually initializes the library. Subsequent calls perform no operation at all. All other API calls return a failure status when the API Library is not initialized.

Prototype

```
int aof16c500kr_init(void);
```

Return Value	Description
0	The operation succeeded.
< 0	An error occurred. This is the negative of <code>errno</code> from <code>errno.h</code> .

Example

```
#include <stdio.h>

#include "20aof16c500kr_dsl.h"

int aof16c500kr_init_dsl(void)
{
    int errs;
    int ret;

    ret = aof16c500kr_init();

    if (ret)
        printf("ERROR: aof16c500kr_init() returned %d\n", ret);

    errs = ret ? 1 : 0;
    return(errs);
}
```

4.6.3. aof16c500kr_ioctl()

This function is the entry point to performing setup and control operations on a 20AOF16C500KR board. This function should only be called after a successful open of the respective device. The specific operation performed varies according to the `request` argument. The `request` argument also governs the use and interpretation of the `arg` argument. The set of supported options for the `request` argument consists of the IOCTL services supported by the driver, which are defined below (section 4.7, page 25).

Prototype

```
int aof16c500kr_ioctl(int fd, int request, void* arg);
```

Argument	Description
<code>fd</code>	This is the file descriptor of the device to access.
<code>request</code>	This specifies the desired operation to be performed.
<code>arg</code>	This is a request specific argument. Refer to the IOCTL services for additional information (section 4.7, page 25).

Return Value	Description
0	The operation succeeded.
< 0	An error occurred. This is the negative of <code>errno</code> from <code>errno.h</code> .

Example

```
#include <stdio.h>

#include "20aof16c500kr_dsl.h"

int aof16c500kr_ioctl_dsl(int fd, int request, void *arg)
{
    int errs;
    int ret;

    ret = aof16c500kr_ioctl(fd, request, arg);
```

```

    if (ret)
        printf("ERROR: aof16c500kr_ioctl() returned %d\n", ret);

    errs    = ret ? 1 : 0;
    return(errs);
}

```

4.6.4. aof16c500kr_open()

This function is the entry point to open a connection to a 20AOF16C500KR board. The device is initialized before the function returns.

Prototype

```
int aof16c500kr_open(int device, int share, int* fd);
```

Argument	Description						
device	This is the zero-based index of the 20AOF16C500KR to access. *						
share	Open the device in Shared Access Mode? If non-zero the device is opened in Shared Access Mode (see below). If zero the device is opened in Exclusive Access Mode (see below).						
fd	The device handle is returned here. The pointer cannot be NULL. Values returned are as follows. <table border="1" data-bbox="451 890 1265 989"> <thead> <tr> <th>Value</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>>= 0</td> <td>This is the handle to use to access the device in subsequent calls.</td> </tr> <tr> <td>-1</td> <td>There was an error. The device is not accessible.</td> </tr> </tbody> </table>	Value	Description	>= 0	This is the handle to use to access the device in subsequent calls.	-1	There was an error. The device is not accessible.
Value	Description						
>= 0	This is the handle to use to access the device in subsequent calls.						
-1	There was an error. The device is not accessible.						

* If the index value is -1, then the API Library accesses /proc/20aof16c500kr.

Return Value	Description
0	The operation succeeded.
< 0	An error occurred. This is the negative of errno from errno.h.

Example

```

#include <stdio.h>

#include "20aof16c500kr_dsl.h"

int aof16c500kr_open_dsl(int device, int share, int* fd)
{
    int errs;
    int ret;

    ret = aof16c500kr_open(device, share, fd);

    if (ret)
        printf("ERROR: aof16c500kr_open() returned %d\n", ret);

    errs    = ret ? 1 : 0;
    return(errs);
}

```

4.6.4.1. Access Modes

Shared Access Mode:

Shared Access Mode allows multiple applications to access the same device simultaneously. In this mode, the first successful open request returns with the device in an initialized state. Subsequent successful Shared Access Mode open requests do not affect the state of the device. Once opened in Shared Access Mode, the device access remains in this mode until all Shared Access Mode accesses release the device with a close request.

Exclusive Access Mode:

Exclusive Access Mode allows a single application to acquire exclusive access to a device. In this mode, a successful open request returns with the device in an initialized state. While open in this mode all subsequent open requests will fail regardless of the access mode requested. Once opened in Exclusive Access Mode, the device access remains in this mode until released by the application with a close request.

4.6.5. aof16c500kr_read()

This function is the entry point to reading data from an open performed on device index -1. This function should only be called after a successful open. The function reads up to `bytes` bytes. The return value is the number of bytes actually read.

NOTE: When performing an open on device index -1, the API Library accesses the `/proc/20aof16c500kr` text file. This read service then reads from that file. Refer to section 2.2, page 12.

NOTE: The read service has no functionality for reading from 20AOF16C500KR devices. Attempts to read from 20AOF16C500KR devices will return an error.

Prototype

```
int aof16c500kr_read(int fd, void *dst, size_t bytes);
```

Argument	Description
<code>fd</code>	This is the file descriptor of the device to access.
<code>dst</code>	The data read will be put here.
<code>bytes</code>	This is the desired number of bytes to read.

Return Value	Description
0 to <code>bytes</code>	The operation succeeded. A value less than <code>bytes</code> indicates that the request timed out.
< 0	An error occurred. This is the negative of <code>errno</code> from <code>errno.h</code> .

Example

```
#include <stdio.h>

#include "20aof16c500kr_dsl.h"

int aof16c500kr_read_dsl(int fd, void* dst, size_t bytes, size_t* qty)
{
    int errs;
    int ret;

    ret = aof16c500kr_read(fd, dst, bytes);
```

```

if (ret < 0)
    printf("ERROR: aof16c500kr_read() returned %d\n", ret);

if (qty)
    qty[0] = (ret < 0) ? 0 : (size_t) ret;

errs    = (ret < 0) ? 1 : 0;
return(errs);
}

```

4.6.6. aof16c500kr_write()

This function is the entry point to writing data to an open 20AOF16C500KR. This function should only be called after a successful open of the respective device. The function writes up to `bytes` bytes to the board. The return value is the number of bytes actually written.

NOTE: When performing an open on device index `-1`, the API Library accesses the `/proc/20aof16c500kr` text file. In this instance, all write requests will fail.

Prototype

```
int aof16c500kr_write(int fd, const void *src, size_t bytes);
```

Argument	Description
<code>fd</code>	This is the file descriptor of the device to access.
<code>src</code>	The data written is taken from here.
<code>bytes</code>	This is the desired number of bytes to write. This must be a multiple of four (4).

Return Value	Description
0 to <code>bytes</code>	The operation succeeded. A value less than <code>bytes</code> indicates that the request timed out.
< 0	An error occurred. This is the negative of <code>errno</code> from <code>errno.h</code> .

Example

```

#include <stdio.h>

#include "20aof16c500kr_dsl.h"

int aof16c500kr_write_dsl(int fd, const void* src, size_t bytes,
size_t* qty)
{
    int errs;
    int ret;

    ret = aof16c500kr_write(fd, src, bytes);

    if (ret < 0)
        printf("ERROR: aof16c500kr_write() returned %d\n", ret);

    if (qty)
        qty[0] = (ret < 0) ? 0 : (size_t) ret;

    errs    = (ret < 0) ? 1 : 0;
}

```

```

    return(errs);
}

```

4.7. IOCTL Services

The 20AOF16C500KR API Library and device driver implement the following IOCTL services. Each service is described along with the applicable `aof16c500kr_ioctl()` function arguments.

4.7.1. AOF16C500KR_IOCTL_AUTO_CALIBRATE

This service initiates an auto-calibration cycle. Most configuration settings should be made before running an auto-calibration cycle. The driver waits for the operation to complete before returning.

NOTE: Do not access the board while an auto-calibration cycle is in progress. Doing so may produce indeterminate results, and may lockup the board.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_AUTO_CALIBRATE
arg	Not used.

4.7.2. AOF16C500KR_IOCTL_AUTO_CAL_STS

This service retrieves the auto-calibration completion status.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_AUTO_CAL_STS
arg	s32*

The value returned will be one of the following.

Value	Description
AOF16C500KR_IOCTL_AUTO_CAL_STS_ACTIVE	Auto-calibration is in progress.
AOF16C500KR_IOCTL_AUTO_CAL_STS_FAIL	Auto-calibration failed.
AOF16C500KR_IOCTL_AUTO_CAL_STS_PASS	Auto-calibration passed.

4.7.3. AOF16C500KR_IOCTL_BUF_CLEAR

This service immediately clears the current content from the output buffer. It also clears the board's buffer overrun and frame overrun status. This service does not halt data output.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_BUF_CLEAR
arg	Not used.

4.7.4. AOF16C500KR_IOCTL_BUF_MODE

This service configures the board's handling of data once it leaves the output buffer.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_BUF_MODE
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_BUF_MODE_CIRC	Buffer data is recycled when it exits the buffer.
AOF16C500KR_BUF_MODE_OPEN	The buffer data is not recycled when it exits the buffer.

4.7.5. AOF16C500KR_IOCTL_BUF_OVER_DATA

This service operates on the Buffer Overflow status.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_BUF_OVER_DATA
arg	s32*

Valid argument values are as follows.

Value	Description
AOF16C500KR_BUF_OVER_DATA_CHK	Report if an overflow has occurred.
AOF16C500KR_BUF_OVER_DATA_CLR	Clear the overflow status.

The following values are those returned when checking on the overflow status.

Value	Description
AOF16C500KR_BUF_OVER_DATA_NO	An overflow did not occur.
AOF16C500KR_BUF_OVER_DATA_YES	An overflow did occur.

4.7.6. AOF16C500KR_IOCTL_BUF_OVER_FRAME

This service operates on the Frame Overflow status.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_BUF_OVER_FRAME
arg	s32*

Valid argument values are as follows.

Value	Description
AOF16C500KR_BUF_OVER_FRAME_CHK	Report if an overflow has occurred.
AOF16C500KR_BUF_OVER_FRAME_CLR	Clear the overflow status.

The following values are those returned when checking on the overflow status.

Value	Description
AOF16C500KR_BUF_OVER_FRAME_NO	An overflow did not occur.
AOF16C500KR_BUF_OVER_FRAME_YES	An overflow did occur.

4.7.7. AOF16C500KR_IOCTL_BUF_SIZE

This service reports the output buffer fill level.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_BUF_SIZE
arg	s32*

The service returns values in the range from zero to 256K.

4.7.8. AOF16C500KR_IOCTL_BUF_THRESH

This service configures the fill level for the output buffer Threshold status. The status is asserted when the fill level exceeds the configured Threshold value.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_BUF_THRESH
arg	s32*

Valid values are from zero to 256K (0x40000) and -1. The value of -1 will retrieve the current setting.

4.7.9. AOF16C500KR_IOCTL_BUF_THR_STS

This service reports the output buffer Threshold status.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_BUF_THR_STS
arg	s32*

The service returns one of the following values.

Value	Description
AOF16C500KR_BUF_THR_STS_CLR	The fill level is at or below the Threshold level.
AOF16C500KR_BUF_THR_STS_SET	The fill level exceeds the Threshold level.

4.7.10. AOF16C500KR_IOCTL_BURST_ENABLE

This service enables or disables output bursting.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_BURST_ENABLE
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current state.
AOF16C500KR_BURST_ENABLE_NO	This refers to output bursting being disabled.
AOF16C500KR_BURST_ENABLE_YES	This refers to output bursting being enabled.

4.7.11. AOF16C500KR_IOCTL_BURST_READY

This service reports the board's readiness for burst initiation.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_BURST_READY
arg	s32*

The service returns one of the following values.

Value	Description
AOF16C500KR_BURST_READY_NO	The board is not ready for burst initiation.
AOF16C500KR_BURST_READY_YES	The board is ready for burst initiation.

4.7.12. AOF16C500KR_IOCTL_BURST_TRIG_SRC

This service controls the trigger source selection for triggered burst operation.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_BURST_TRIG_SRC
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_BURST_TRIG_SRC_EXT	Utilize external burst triggering.
AOF16C500KR_BURST_TRIG_SRC_RAG	Utilize the Rate-A Generator output.
AOF16C500KR_BURST_TRIG_SRC_RBG	Utilize the Rate-B Generator output.

4.7.13. AOF16C500KR_IOCTL_CHANNEL_SEL

This service enables or disables channels for outputting data.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_CHANNEL_SEL
arg	s32*

Valid argument values are any valid set of bits for the set of supported channels, and -1. If a bit is set, then the corresponding channel is enabled. A zero bit disables the channel. The lowest significant bit corresponds to channel zero. The value -1 is used to retrieve the current setting.

4.7.14. AOF16C500KR_IOCTL_CLOCK_ENABLE

This service enables and disables clocking of output data.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_CLOCK_ENABLE
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_CLOCK_ENABLE_NO	This disables the output sample clock.
AOF16C500KR_CLOCK_ENABLE_YES	This enables the output sample clock.

4.7.15. AOF16C500KR_IOCTL_CLOCK_READY

This service reports the board's readiness to accept a clock.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_CLOCK_READY
arg	s32*

The service returns one of the following values.

Value	Description
AOF16C500KR_CLOCK_READY_NO	The board is not ready for a clock.
AOF16C500KR_CLOCK_READY_YES	The board is ready for a clock.

4.7.16. AOF16C500KR_IOCTL_CLOCK_SRC

This service selects the source for the output sample clock.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_CLOCK_SRC
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_CLOCK_SRC_EXT	This selects the external clock input as the clock source.
AOF16C500KR_CLOCK_SRC_RAG	This selects the Rate-A Generator as the source.
AOF16C500KR_CLOCK_SRC_RBG	This selects the Rate-B Generator as the source.

4.7.17. AOF16C500KR_IOCTL_CLOCK_SW

This service initiates an output clock cycle. The service waits for up to the write timeout period for the operation to complete (though not the infinite option). (See AOF16C500KR_IOCTL_TX_IO_TIMEOUT, section 4.7.44, page 39.)

Usage

Argument	Description
request	AOF16C500KR_IOCTL_CLOCK_SW
arg	Not used.

4.7.18. AOF16C500KR_IOCTL_DATA_FORMAT

This service sets the data encoding format.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_DATA_FORMAT
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_DATA_FORMAT_2S_COMP	Select the Twos Compliment data format.
AOF16C500KR_DATA_FORMAT_OFF_BIN	Select the Offset Binary encoding format.

4.7.19. AOF16C500KR_IOCTL_DIO_DIR_OUT

This service configures the direction of the digital I/O signals.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_DIO_DIR_OUT
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_DIO_DIR_OUT_D3_D0	DIO lines D3 through D0 are output and the others are input.
AOF16C500KR_DIO_DIR_OUT_D7_D4	DIO lines D7 through D4 are output and the others are input.
AOF16C500KR_DIO_DIR_OUT_D7_D0	DIO lines D7 through D0 are output.
AOF16C500KR_DIO_DIR_OUT_NONE	All DIO lines are inputs.

4.7.20. AOF16C500KR_IOCTL_DIO_READ

This service reads the value of the eight digital I/O lines.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_DIO_READ
arg	s32*

The value returned is from 0x00 through 0xFF. The bit values read are the levels at the cable interface for those bits configured as inputs and the last value written for those configured as outputs.

4.7.21. AOF16C500KR_IOCTL_DIO_WRITE

This service writes a value to the eight digital I/O lines.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_DIO_WRITE
arg	s32*

Valid argument values are 0x00 through 0xFF. All bit values are latched and appear at the cable interface only for when configured as outputs.

4.7.22. AOF16C500KR_IOCTL_FILTER

This service enables or disables the output filter.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_FILTER
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_FILTER_DISABLE	This disables the output filter.
AOF16C500KR_FILTER_ENABLE	This enables the output filter.

4.7.23. AOF16C500KR_IOCTL_GEN_A_ENABLE

This service enables or disables the Rate-A Generator.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_GEN_A_ENABLE
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.

AOF16C500KR_GEN_ENABLE_NO	This disables the rate generator.
AOF16C500KR_GEN_ENABLE_YES	This enables the rate generator.

4.7.24. AOF16C500KR_IOCTL_GEN_A_NDIV

This service sets the NDIV value for the Rate-A Generator.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_GEN_A_NDIV
arg	s32*

Valid argument values are in the range from 98 to 0xFFFFFFFF, and -1. The value -1 is used to retrieve the current setting.

4.7.25. AOF16C500KR_IOCTL_GEN_B_ENABLE

This service enables or disables the Rate-B Generator.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_GEN_B_ENABLE
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_GEN_ENABLE_NO	This disables the rate generator.
AOF16C500KR_GEN_ENABLE_YES	This enables the rate generator.

4.7.26. AOF16C500KR_IOCTL_GEN_B_NDIV

This service sets the NDIV value for the Rate-B Generator.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_GEN_B_NDIV
arg	s32*

Valid argument values are in the range from 98 to 0xFFFFFFFF, and -1. The value -1 is used to retrieve the current setting.

4.7.27. AOF16C500KR_IOCTL_GROUND_SENSE

This service configures the board's ground sense logic.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_GROUND_SENSE
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_GROUND_SENSE_DISABLE	This disables remote ground sensing.
AOF16C500KR_GROUND_SENSE_REMOTE	This enables remote ground sensing.

4.7.28. AOF16C500KR_IOCTL_INITIALIZE

This service returns all driver interface settings for the board to the state they were in when the board was first opened. This includes both hardware-based settings and software-based settings.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_INITIALIZE
arg	Not used.

4.7.29. AOF16C500KR_IOCTL_IRQ_SEL

This service enables and disabled firmware interrupts. Interrupts referenced in the request are enabled. All others are disabled.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_IRQ_SEL
arg	s32*

Valid argument values include any combination of the options listed in the table below, and -1. The value -1 is used to retrieve the current setting.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_IRQ_AUTO_CAL_DONE	This refers to the completion of auto-calibration.
AOF16C500KR_IRQ_BUF_ERROR	This refers to the occurrence of a Buffer Overflow or of a Frame Overflow.
AOF16C500KR_IRQ_BUF_THR_H2L	This refers to the buffer fill level dropping to the Threshold level.
AOF16C500KR_IRQ_BUF_THR_L2H	This refers to the buffer fill level rising above the Threshold level.
AOF16C500KR_IRQ_BURST_READY	This refers to the board becoming ready for a burst trigger.
AOF16C500KR_IRQ_DIO0_L2H	This refers to a low to high transition at the D0 digital I/O line.
AOF16C500KR_IRQ_LOAD_READY_H2L	This refers to a circular buffer becoming not ready to receive data.
AOF16C500KR_IRQ_LOAD_READY_L2H	This refers to a circular buffer becoming ready to receive data.

4.7.30. AOF16C500KR_IOCTL_LED

This service configures the LED at the board's front panel interface.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_LED
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_LED_OFF	This turns the LED off.
AOF16C500KR_LED_ON	This turns the LED on.

4.7.31. AOF16C500KR_IOCTL_LOAD_READY

This service reports the buffer's readiness to receive additional data when in circular buffer mode.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_LOAD_READY
arg	s32*

Valid values returned by the service are as follows.

Value	Description
AOF16C500KR_LOAD_READY_NO	The buffer is not ready to receive additional data.
AOF16C500KR_LOAD_READY_YES	The buffer is ready to receive additional data.

4.7.32. AOF16C500KR_IOCTL_LOAD_REQUEST

This service requests that the buffer become ready to receive additional data when in circular buffer mode. The service waits for up to the write timeout period for the operation to complete (though not the infinite option). (See AOF16C500KR_IOCTL_TX_IO_TIMEOUT, section 4.7.44, page 39.)

Usage

Argument	Description
request	AOF16C500KR_IOCTL_LOAD_REQUEST
arg	Not used.

4.7.33. AOF16C500KR_IOCTL_OUTPUT_MODE

This service configures the buffer's data output mode.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_OUTPUT_MODE
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_OUTPUT_MODE_SEQ	Channel data is output to one channel at a time, sequentially. *
AOF16C500KR_OUTPUT_MODE_SIM	Channel data is output to all channels simultaneously.

* Refer to the hardware reference manual to see how this affects the sample rate.

4.7.34. AOF16C500KR_IOCTL_QUERY

This service queries the driver for various pieces of information about the board and the driver.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_QUERY
arg	s32*

Valid argument values are as follows.

Value	Description
AOF16C500KR_QUERY_AO_CONFIG	This returns the board's output configuration. See below.
AOF16C500KR_QUERY_AUTO_CAL_MS	This returns the maximum duration of the Auto Calibration cycle in milliseconds.
AOF16C500KR_QUERY_CHANNEL_MAX	This returns the maximum number of output channels supported by the board.
AOF16C500KR_QUERY_CHANNEL_QTY	This returns the actual number of output channels on the current board.
AOF16C500KR_QUERY_COUNT	This returns the number of query options supported by the IOCTL service.
AOF16C500KR_QUERY_CUSTOM_FEAT	This returns information on the board's custom features. See below.
AOF16C500KR_QUERY_DEVICE_TYPE	This returns the identifier value for the board's type. The value should be GSC_DEV_TYPE_20AOF16C500KR.
AOF16C500KR_QUERY_FGEN_MAX	This gives the maximum rate generator frequency.
AOF16C500KR_QUERY_FGEN_MIN	This gives the minimum rate generator frequency.
AOF16C500KR_QUERY_FIFO_SIZE	This returns the size of the output buffer in samples.
AOF16C500KR_QUERY_FILTER	This returns information on the installed filter option. See below.
AOF16C500KR_QUERY_FREF_DEFAULT	This gives the default FREF value in hertz.
AOF16C500KR_QUERY_FSAMP_MAX	This gives the maximum sample rate in S/S.
AOF16C500KR_QUERY_FSAMP_MIN	This gives the minimum sample rate in S/S.
AOF16C500KR_QUERY_INIT_MS	This returns the duration of a board initialization in milliseconds.
AOF16C500KR_QUERY_NDIV_MAX	This returns the maximum supported NDIV value.
AOF16C500KR_QUERY_NDIV_MIN	This returns the minimum supported NDIV value.
AOF16C500KR_QUERY_RANGE	This returns information on the board's configured voltage range. See below.

Valid return values for the AOF16C500KR_QUERY_AO_CONFIG option are as follows.

Value	Description
AOF16C500KR_AO_CONFIG_DIFF	The board is factory configured for differential operation.
AOF16C500KR_AO_CONFIG_SE	The board is factory configured for single ended operation.

Valid return values for the AOF16C500KR_QUERY_CUSTOM_FEAT option are as follows.

Value	Description
	No custom options are defined at this time.

Valid return values for the AOF16C500KR_QUERY_FILTER option are as follows.

Value	Description
AOF16C500KR_FILTER_140K	The installed filter is a 140K, elliptic, 8 th order type.

Valid return values for the AOF16C500KR_QUERY_RANGE option are as follows.

Value	Description
AOF16C500KR_RANGE_6_3	The board is factory configured for ± 6 and ± 3 volts.
AOF16C500KR_RANGE_10_5	The board is factory configured for ± 10 and ± 5 volts.

Valid return values are as indicated in the above tables and as given in the below table.

Value	Description
AOF16C500KR_IOCTL_QUERY_ERROR	Either there was a processing error or the query option is unrecognized.

4.7.35. AOF16C500KR_IOCTL_RANGE

This service configures the board's output voltage range.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_RANGE
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_RANGE_3	This selects the ± 3 -volt range. †
AOF16C500KR_RANGE_5	This selects the ± 5 -volt range. ‡
AOF16C500KR_RANGE_6	This selects the ± 6 -volt range. †
AOF16C500KR_RANGE_10	This selects the ± 10 -volt range. ‡

† This option is available only for boards factory configured for ± 6 volts and ± 3 volts.

‡ This option is available only for boards factory configured for ± 10 volts and ± 5 volts.

4.7.36. AOF16C500KR_IOCTL_REG_MOD

This service performs a read-modify-write of a 20AOF16C500KR register. This includes only the GSC firmware registers. The PCI and PLX Feature Set Registers are read-only. Refer to 20aof16c500kr.h for a complete list of the GSC firmware registers.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_REG_MOD
arg	gsc reg t*

Definition

```
typedef struct
{
    u32 reg;
    u32 value;
    u32 mask;
} gsc_reg_t;
```

Fields	Description
reg	This is set to the identifier for the register to access.
value	This contains the value for the register bits to modify.
mask	This specifies the set of bits to modify. If a bit here is set, then the respective register bits is modified. If a bit here is zero, then the respective register bit is unmodified.

4.7.37. AOF16C500KR_IOCTL_REG_READ

This service reads the value of a 20AOF16C500KR register. This includes the PCI registers, the PLX Feature Set Registers and the GSC firmware registers. Refer to `20aof16c500kr.h` and `gsc_pci9656.h` for the complete list of accessible registers.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_REG_READ
arg	<code>gsc_reg_t*</code>

Definition

```
typedef struct
{
    u32 reg;
    u32 value;
    u32 mask;
} gsc_reg_t;
```

Fields	Description
reg	This is set to the identifier for the register to access.
value	This is the value read from the specified register.
mask	This is ignored for read request.

4.7.38. AOF16C500KR_IOCTL_REG_WRITE

This service writes a value to a 20AOF16C500KR register. This includes only the GSC firmware registers. The PCI and PLX Feature Set Registers are read-only. Refer to `20aof16c500kr.h` for a complete list of the GSC firmware registers.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_REG_WRITE
arg	<code>gsc_reg_t*</code>

Definition

```
typedef struct
{
    u32 reg;
    u32 value;
    u32 mask;
} gsc_reg_t;
```

Fields	Description
reg	This is set to the identifier for the register to access.
value	This is the value to write to the specified register.
mask	This is ignored for write request.

4.7.39. AOF16C500KR_IOCTL_TRIGGER_SW

This service initiates an output burst cycle. The service waits for up to the write timeout period for the operation to complete (though not the infinite option). (See AOF16C500KR_IOCTL_TX_IO_TIMEOUT, section 4.7.44, page 39.)

Usage

Argument	Description
request	AOF16C500KR_IOCTL_TRIGGER_SW
arg	Not used.

4.7.40. AOF16C500KR_IOCTL_TX_IO_ABORT

This service aborts an ongoing `write()` request.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_TX_IO_ABORT
arg	s32*

The results are reported as one of the following values.

Value	Description
AOF16C500KR_IOCTL_TX_IO_ABORT_NO	A <code>write()</code> request was not aborted as none were ongoing.
AOF16C500KR_IOCTL_TX_IO_ABORT_YES	An ongoing <code>write()</code> request was aborted.

4.7.41. AOF16C500KR_IOCTL_TX_IO_MODE

This service sets the I/O mode used for data write requests.

NOTE: Applications may experience improved responsiveness with write requests by coordinating the buffer Threshold setting with the number of samples in the write request.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_TX_IO_MODE
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
GSC IO MODE BMDMA	Use Block Mode DMA.
GSC IO MODE DMDMA	Use Demand Mode DMA.
GSC IO MODE PIO	Use PIO mode, which is repetitive register access. This is the default.

4.7.42. AOF16C500KR_IOCTL_TX_IO_OVR_DAT

This service configures the write service to check for an output buffer data overflow before performing write operations. Sample data is lost when there is a buffer overflow.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_TX_IO_OVR_DAT
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_IOCTL_TX_IO_OVR_DAT_CHECK	Perform the check. This is the default.
AOF16C500KR_IOCTL_TX_IO_OVR_DAT_IGNORE	Do not perform the check.

4.7.43. AOF16C500KR_IOCTL_TX_IO_OVR_FRM

This service configures the write service to check for a frame overflow before performing write operations. Sample data is lost when there is a frame overflow.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_TX_IO_OVR_FRM
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_IOCTL_TX_IO_OVR_FRM_CHECK	Perform the check. This is the default.
AOF16C500KR_IOCTL_TX_IO_OVR_FRM_IGNORE	Do not perform the check.

4.7.44. AOF16C500KR_IOCTL_TX_IO_TIMEOUT

This service sets the timeout limit for data write requests. The value is expressed in seconds.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_TX_IO_TIMEOUT
arg	s32*

Valid argument values are in the range from zero to 3600, -1, and `AOF16C500KR_IO_TIMEOUT_INFINITE`. A value of zero tells the driver not to sleep in order to wait for more space. A value of -1 is used to retrieve the current setting. If the option `AOF16C500KR_IO_TIMEOUT_INFINITE` is used, then the driver will wait indefinitely rather than timing out. The default is 10 seconds.

4.7.45. AOF16C500KR_IOCTL_WAIT_CANCEL

This service resumes all threads blocked via `AOF16C500KR_IOCTL_WAIT_EVENT` IOCTL calls (section 4.7.46, page 40), according to the provided criteria. When a blocked thread is waiting for any event specified in the structure, then the thread is resumed.

NOTE: The driver itself makes use of the wait services for various internal operations. Driver initiated waits are unaffected by application cancel requests.

Usage

Argument	Description
request	<code>AOF16C500KR_IOCTL_WAIT_CANCEL</code>
arg	<code>gsc wait t*</code>

Definition

```
typedef struct
{
    u32  flags;
    u32  main;
    u32  gsc;
    u32  alt;
    u32  io;
    u32  timeout_ms;
    u32  count;
} gsc_wait_t;
```

Fields	Description
flags	This is unused by wait cancel operations.
main	This specifies the set of <code>GSC_WAIT_MAIN_*</code> events whose wait requests are to be cancelled. Refer to section 4.7.46.2 on page 41.
gsc	This specifies the set of <code>AOF16C500KR_WAIT_GSC_*</code> events whose wait requests are to be cancelled. Refer to section 4.7.46.3 on page 42.
alt	This is unused by the 20AOF16C500KR driver and should be zero.
io	This specifies the set of <code>AOF16C500KR_WAIT_IO_*</code> events whose wait requests are to be cancelled. Refer to section 4.7.46.4 on page 42.
timeout_ms	This is unused by wait cancel operations.
count	Upon return this indicates the number of waits that were cancelled.

4.7.46. AOF16C500KR_IOCTL_WAIT_EVENT

This service blocks a thread until any one of a specified set of events occurs, or until a timeout lapses, whichever occurs first. The set of possible events to wait for are specified in the structure's `main`, `gsc`, `alt` and `io` fields. All field values must be valid and at least one event must be specified. If the thread is resumed because one of the referenced events has occurred, then the bit for the respective event is the only event bit that will be set. All other event bits and fields will be zero. (Multiple event bits will be set only if the events occur simultaneously.)

NOTE: The service waits only for the first of the specified events, not for all specified events.

NOTE: A wait timeout is reported via the `gsc_wait_t` structure's `flags` field having the `GSC_WAIT_FLAG_TIMEOUT` flag set, rather than via an `ETIMEDOUT` error.

Usage

Argument	Description
<code>request</code>	<code>AOF16C500KR_IOCTL_WAIT_EVENT</code>
<code>arg</code>	<code>gsc_wait_t*</code>

Definition

```
typedef struct
{
    u32 flags;
    u32 main;
    u32 gsc;
    u32 alt;
    u32 io;
    u32 timeout_ms;
    u32 count;
} gsc_wait_t;
```

Fields	Description
<code>flags</code>	This must initially be zero. Upon return this indicates the reason that the thread was resumed. Refer to section 4.7.46.1 on page 41.
<code>main</code>	This specifies any number of <code>GSC_WAIT_MAIN_*</code> events that the thread is to wait for. Refer to section 4.7.46.2 on page 41.
<code>gsc</code>	This specifies any number of <code>AOF16C500KR_WAIT_GSC_*</code> events that the thread is to wait for. Refer to section 4.7.46.3 on page 42.
<code>alt</code>	This is unused by the 20AOF16C500KR driver and must be zero.
<code>io</code>	This specifies any number of <code>AOF16C500KR_WAIT_IO_*</code> events that the thread is to wait for. Refer to section 4.7.46.4 on page 42.
<code>timeout_ms</code>	This specified the maximum amount of time, in milliseconds, that the thread is to wait for any of the referenced events. A value of zero means do not timeout at all. If non-zero, then upon return the value will be the approximate amount of time actually waited.
<code>count</code>	This is unused by wait event operations and must be zero.

4.7.46.1. `gsc_wait_t.flags` Options

Upon return from a wait request the wait structure's `flags` field will indicate the reason that the thread was resumed. Only one of the below options will be set.

Fields	Description
<code>GSC_WAIT_FLAG_CANCEL</code>	The wait request was cancelled.
<code>GSC_WAIT_FLAG_DONE</code>	One of the referenced events occurred.
<code>GSC_WAIT_FLAG_TIMEOUT</code>	The timeout period lapsed before a referenced event occurred.

4.7.46.2. `gsc_wait_t.main` Options

The wait structure's `main` field may specify any of the below primary interrupt options. These interrupt options are supported by the 20AOF16C500KR and other General Standards products.

Fields	Description
<code>GSC_WAIT_MAIN_DMA0</code>	This refers to the DMA Done interrupt on DMA engine number zero.

GSC_WAIT_MAIN_DMA1	This refers to the DMA Done interrupt on DMA engine number one.
GSC_WAIT_MAIN_GSC	This refers to any of the Interrupt Control/Status Register interrupts.
GSC_WAIT_MAIN_OTHER	This generally refers to an interrupt generated by another device sharing the same interrupt as the 20AOF16C500KR.
GSC_WAIT_MAIN_PCI	This refers to any interrupt generated by the 20AOF16C500KR.
GSC_WAIT_MAIN_SPURIOUS	This refers to board interrupts which should never be generated.
GSC_WAIT_MAIN_UNKNOWN	This refers to board interrupts whose source could not be identified.

4.7.46.3. gsc_wait_t.gsc Options

The wait structure's `gsc` field may specify any combination of the below interrupt options. These are the interrupt options referenced in the Board Control Register. Applications are responsible for selecting the desired interrupt options. Refer to `AOF16C500KR_IOCTL_IRQ_SEL` (section 4.7.29, page 33).

Value	Description
AOF16C500KR_WAIT_GSC_AUTO_CAL_DN	This refers to the completion of auto-calibration.
AOF16C500KR_WAIT_GSC_BUF_ERROR	This refers to the occurrence of a buffer overflow or a frame overflow.
AOF16C500KR_WAIT_GSC_BUF_THR_H2L	This refers to buffer fill level falling to the Threshold level.
AOF16C500KR_WAIT_GSC_BUF_THR_L2H	This refers to buffer fill level rising above the Threshold level.
AOF16C500KR_WAIT_GSC_BURST_READY	This refers to the board becoming ready for a burst trigger.
AOF16C500KR_WAIT_GSC_DIO0_L2H	This refers to a low to high transition on digital I/O line D0.
AOF16C500KR_WAIT_GSC_LD_RDY_H2L	This refers to a circular buffer becoming not ready to receive data.
AOF16C500KR_WAIT_GSC_LD_RDY_L2H	This refers to a circular buffer becoming ready to receive data.

4.7.46.4. gsc_wait_t.io Options

The wait structure's `io` field may specify any of the below event options. These events are generated in response to application board data read requests.

Fields	Description
AOF16C500KR_WAIT_IO_TX_ABORT	This refers to write requests which have been aborted.
AOF16C500KR_WAIT_IO_TX_DONE	This refers to write requests which have been satisfied.
AOF16C500KR_WAIT_IO_TX_ERROR	This refers to write requests which end due to an error.
AOF16C500KR_WAIT_IO_TX_TIMEOUT	This refers to write requests which end due to the timeout period lapse.

4.7.47. AOF16C500KR_IOCTL_WAIT_STATUS

This service counts all threads blocked via the `AOF16C500KR_IOCTL_WAIT_EVENT` IOCTL service (section 4.7.46, page 40), according to the provided criteria. A match is made when a waiting thread's wait criteria matches any of the criteria specified in the structure passed to this service.

NOTE: The driver itself makes use of the wait services for various internal operations. Driver initiated waits are ignored by application status requests.

Usage

Argument	Description
<code>request</code>	<code>AOF16C500KR_IOCTL_WAIT_STATUS</code>
<code>arg</code>	<code>gsc wait t*</code>

Definition

```
typedef struct
{
    u32  flags;
    u32  main;
    u32  gsc;
    u32  alt;
    u32  io;
    u32  timeout_ms;
    u32  count;
} gsc_wait_t;
```

Fields	Description
flags	This is unused by wait status operations.
main	This specifies the set of GSC_WAIT_MAIN_* events whose wait requests are to be counted. Refer to section 4.7.46.2 on page 41.
gsc	This specifies the set of AOF16C500KR_WAIT_GSC_* events whose wait requests are to be counted. Refer to section 4.7.46.3 on page 42.
alt	This is unused by the 20AOF16C500KR driver and should be zero.
io	This specifies the set of AOF16C500KR_WAIT_IO_* events whose wait requests are to be counted. Refer to section 4.7.46.4 on page 42.
timeout_ms	This is unused by wait status operations.
count	Upon return this indicates the number of waits that met any of the specified criteria.

4.7.48. AOF16C500KR_IOCTL_XCVR_OUTPUT

This service enables or disables the clock and trigger output signals at the cable interface.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_XCVR_OUTPUT
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_IOCTL_XCVR_OUTPUT_DISABLE	This disables the transceivers.
AOF16C500KR_IOCTL_XCVR_OUTPUT_ENABLE	This enables the transceivers.

4.7.49. AOF16C500KR_IOCTL_XCVR_POL

This service configures the polarity of the clock and trigger signals at the cable interface.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_XCVR_POL
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_XCVR_POL_DEF	This selects the signals' default polarities.
AOF16C500KR_XCVR_POL_INV	This inverts the signals from their default polarities.

4.7.50. AOF16C500KR_IOCTL_XCVR_TYPE

This service selects TTL or LVDS signaling on the external clock and trigger signals.

Usage

Argument	Description
request	AOF16C500KR_IOCTL_XCVR_TYPE
arg	s32*

Valid argument values are as follows.

Value	Description
-1	Retrieve the current setting.
AOF16C500KR_XCVR_TYPE_LVDS	Use LVDS signaling.
AOF16C500KR_XCVR_TYPE_TTL	Use TTL signaling.

5. The Driver

NOTE: Contact General Standards Corporation if additional driver functionality is required.

5.1. Files

The device driver source files are summarized in the table below.

File	Description
driver/*.c	The driver source files.
driver/*.h	The driver header files.
driver/20aof16c500kr.h	This is the driver interface header file.
driver/Makefile	This is the driver make file.
driver/start	Shell script to install the driver executable and device nodes.
driver/20aof16c500kr.ko	This is the driver executable (kernel 2.6 and later).
driver/20aof16c500kr.o	This is the driver executable (kernel 2.4 and earlier).

5.2. Build

NOTE: Building the driver requires installation of the kernel sources.

The device driver is built via the Overall Make Script (section 2.7, page 13), but can be built separately following the below steps.

1. Change to the directory where the driver and its sources are installed (.../driver/).
2. Remove existing build targets by issuing the below command.

```
make clean
```

3. Build the driver by issuing the below command.

```
make
```

NOTE: Due to the differences between the many Linux distributions some build errors may occur. These errors may include system header location differences, which should be easily corrected.

5.3. Startup

NOTE: The driver will have to be built before being used as it is provided in source form only.

The startup script used in this procedure is designed to ensure that the driver module in the install directory is the module that is loaded. This is accomplished by making sure that an already loaded module is first unloaded before attempting to load the module from the disk drive. In addition, the script also deletes and recreates the device nodes. This is done to ensure that the device nodes in use have the same major number as assigned dynamically to the driver by the kernel, and so that the number of device nodes correspond to the number of boards identified by the driver.

5.3.1. Manual Driver Startup Procedures

Start the driver manually by following the below listed steps.

NOTE: The following steps may require elevated privileges.

1. Change to the directory where the driver sources are installed (.../driver/).
2. Install the driver module and create the device nodes by executing the below command. If any errors are encountered then an appropriate error message will be displayed.

```
./start
```

NOTE: This script must be executed each time the host is rebooted.

NOTE: The 20AOF16C500KR device node major number is assigned dynamically by the kernel. The minor numbers and the device node suffix numbers are index numbers beginning with zero, and increase by one for each additional board installed.

3. Verify that the device driver module has been loaded by issuing the below command and examining the output. The module name `20aof16c500kr` should be included in the output.

```
lsmod
```

4. Verify that the device nodes have been created by issuing the below command and examining the output. The output should include one node for each installed board.

```
ls -l /dev/20aof16c500kr.*
```

5.3.2. Automatic Driver Startup Procedures

Start the driver automatically with each system reboot by following the below listed steps.

1. Locate and edit the system startup script `rc.local`, which should be in the `/etc/rc.d/` directory. Modify the file by adding the below line so that it is executed with every reboot. The example is based on the driver being installed in `/usr/src/linux/drivers/`, though it may have been installed elsewhere.

```
/usr/src/linux/drivers/20aof16c500kr/driver/start
```

NOTE: For `systemd` installations the file `rc.local` may be located under the `/etc/` directory rather than under `/etc/rc.d/`.

2. Load the driver and create the required device nodes by rebooting the system.
3. Verify that the driver is loaded and that the device nodes have been created. Do this by following the verification steps given in the manual startup procedures.

5.3.2.1. File `rc.local` Not Present

Some distributions may not install a default version of `rc.local`. Some may not even create the directory `/etc/rc.d/`. If the directory is not present, then it may be created. The directory must be created with the owner and group set to `root`. The directory permissions must be set to `rxr-xr-x`. If the file `/etc/rc.d/rc.local` is not present, then it too may be created. The file must also be created with the owner and group set to `root`. Additionally, the file permissions must also be set to `rxr-xr-x`. After the directory and file are created as described, reboot to verify boot time loading of the driver. Here is an example of a default version of `rc.local`.

```
#!/bin/bash
# Add you local content here.
```

5.3.2.2. Default `rc.local` File Permissions

The `rc.local` script may fail to run at boot time because some distributions install a default version of the file without execute permissions. Without execute permissions, boot time invocation of the script fails, which inhibits boot time loading of the driver. If this is the case, then change the file permissions to `rwxr-xr-x`. After the file permissions are adjusted as described, reboot to verify boot time loading of the driver.

5.3.2.3. `systemd` Installations

With the advent of the `systemd` startup implementation, `rc.local` may be accessed via a `systemd` startup service. The service name may be `rc-local`, `rc-local.service` or something similar. This service may or may not be enabled by default. If the service is disabled, then the script will not execute, which prevents boot time loading of the driver. The service can be enabled with the below command line. After the service is enabled, reboot to verify boot time loading of the driver.

```
systemctl enable rc-local
```

NOTE: For `systemd` installations the file `rc.local` may be located under the `/etc/` directory rather than under `/etc/rc.d/`.

5.3.2.4. `systemd` and `rc.local` Timing

If the above steps have been performed but the driver still does not start then examine the `dmesg` output for driver messages. If the output shows that the driver starts and immediately stops, then the problem may be timing. That is, since `systemd` doesn't serialize startup initialization as done in the past, driver loading may fail if required services have not completed their own initialization. If this is the problem, then it may be corrected simply by inserting a delay in `rc.local` prior to it calling the driver's start script (i.e., `sleep` for one or more seconds).

5.3.2.5. SELinux Implications

If not disabled, then SELinux may prevent boot time loading of the driver. If this is the case, then it can be verified and corrected using SELinux related tools and utilities. First, install the necessary software using the below command. (As necessary, replace the `yum` command line with that which is available for your distribution.)

```
yum install setroubleshoot setools
```

Next, run the below command to determine if SELinux is preventing the driver from loading at boot time.

```
sealert -a /var/log/audit/audit.log
```

If SELinux is preventing the driver from loading, then the output from the above command should include a reference to the driver's start script, the `insmod` command that loads the driver or the name of the driver executable. If so, then the output should also indicate the commands necessary to resolve the issue. The following is an example of the instructions given when the culprit is `insmod`, which is the start script command that loads the driver. After running these commands reboot the system to verify boot time loading of the driver.

```
ausearch -c 'insmod' --raw | audit2allow -M my-insmod
semodule -X 300 -i my-insmod.pp
```

5.4. Verification

Follow the below steps to verify that the driver has been properly installed and started.

1. Verify that the file `/proc/20aof16c500kr` is present. If the file is present then the driver is loaded and running. Verify the file's presence by viewing its content with the below command.

```
cat /proc/20aof16c500kr
```

5.5. Version

The driver version number can be obtained in a variety of ways. It is reported by the driver both when the driver is loaded and when it is unloaded (depending on kernel configuration options, this may be visible only in places such as `/var/log/messages`). It is reported in the text file `/proc/20aof16c500kr` while the driver is loaded and running. The version number is also given in the file `release.txt` in the root install directory.

5.6. Shutdown

Shutdown the driver following the below listed steps.

NOTE: The following steps may require elevated privileges.

1. If the driver is currently loaded then issue the below command to unload the driver.

```
rmmod 20aof16c500kr
```

2. Verify that the driver module has been unloaded by issuing the below command. The module name `20aof16c500kr` should not be in the listed output.

```
lsmod
```

6. Document Source Code Examples

The source code examples included in this document are built into a statically linkable library usable with console applications. The purpose of these files is to verify that the documentation samples compile and to provide a library of working sample code to assist in a user's learning curve and application development effort.

6.1. Files

The library files are summarized in the table below.

File	Description
docsrc/*.c	These are the C source files.
docsrc/makefile	This is the library make file.
docsrc/makefile.dep	This is an automatically generated make dependency file.
include/20aof16c500kr_dsl.h	This is the primary utility header file.
lib/20aof16c500kr_dsl.a	This is the statically linkable library file.

6.2. Build

The library is built via the Overall Make Script (section 2.7, page 13), but can be built separately following the below steps.

1. Change to the directory where the documentation sources are installed (.../docsrc/).
2. Remove existing build targets by issuing the below command.

```
make clean
```

3. Compile the sample files and build the library by issuing the below command.

```
make
```

4. Rebuild the Main Library (section 3.2.1, page 16).

6.3. Library Use

The library is used both at application compile time and at application link time. At compile time include the below listed header file in each source file using a component of the library interface. At link time include the below listed library file with the objects being linked with the application.

Description	File	Location
Header File	20aof16c500kr_dsl.h	.../include/
Static Link Library	20aof16c500kr_dsl.a	.../lib/

7. Utility Source Code

The driver archive includes a body of utility services built into a statically linkable library that is usable with console applications. The primary purpose of the services is both for code reuse in the sample applications and to provide wrappers, mostly visual, around the driver's IOCTL services. The aim of the visual wrappers is to facilitate structured console output for the sample applications. An additional purpose of these utility services is to provide a library of working sample code to assist in a user's learning curve and application development effort.

7.1. Files

The library files are summarized in the table below.

File	Description
utils/util_*.c	These are device specific utility source files.
utils/gsc_*.c	These are device and OS independent utility source files.
utils/os_*.c	These are OS specific utility source files.
utils/makefile	This is the library make file.
utils/makefile.dep	This is an automatically generated make dependency file.
include/20aof16c500kr_utils.h	This is the primary utility header file.
lib/20aof16c500kr_utils.a	This is the statically linkable library file.

7.2. Build

The library is built via the Overall Make Script (section 2.7, page 13), but can be built separately following the below steps.

1. Change to the directory where the utility sources are installed (.../utils/).
2. Remove existing build targets by issuing the below command.

```
make clean
```

3. Compile the sample files and build the library by issuing the below command.

```
make
```

4. Rebuild the Main Library (section 3.2.1, page 16).

7.3. Library Use

The library is used both at application compile time and at application link time. At compile time include the below listed header file in each source file using a component of the library interface. At link time include the below listed library files with the objects being linked with the application.

Description	File	Location
Header File	20aof16c500kr_utils.h	.../include/
Static Link Libraries	20aof16c500kr_utils.a gsc_utils.a os_utils.a plx_utils.a	.../lib/

8. Operating Information

This section explains some basic operational procedures for using the 20AOF16C500KR. This is in no way intended to be a comprehensive guide. This is simply to address a very few issues relating to their use.

8.1. Debugging Aids

The driver package includes the following items useful for development and/or debugging aids.

8.1.1. Device Identification

When communicating with technical support complete device identification is virtually always necessary. The *id* example application is provided for this specific purpose. This is a text only console application. The output can be piped to a file, which can then be emailed to GSC technical support when requested. Locate the application as follows.

Description	File	Location
Application	id	.../id/

8.1.2. Detailed Register Dump

Among the utility services provided is a function to generate a detailed listing of the board's registers to the console. When used, the function is typically used to verify the board's configuration. In these cases, the function should be called just prior to the first read or write operation. When intended for sending to GSC tech support, please set the *detail* argument to 1. The function arguments are as follows. The utility location is given in the subsequent table.

Argument	Description
fd	This is the file descriptor used to access the device.
detail	If non-zero the GSC register dump will include details of each register field.

Description	File/Name	Location
Function	aof16c500kr_reg_list()	Source File
Source File	util_reg.c	.../utils/
Header File	20aof16c500kr_utils.h	.../include/
Library File	20aof16c500kr_utils.a	.../lib/

8.2. Analog Output Configuration

The basic steps for Analog Output configuration are illustrated in the utility function noted below. The table also gives the location of the source file, the header file and the corresponding library containing the executable code.

Item	Name/File	Location
Function	aof16c500kr_config_ao()	Source File
Source File	util_config_ao.c	.../utils/
Header File	20aof16c500kr_utils.h	.../include/
Library File	20aof16c500kr_utils.a	.../lib/

8.3. I/O Modes

All data write requests move the requested data from application memory, to an intermediate driver buffer, then from there to the board's output buffer. The data is processed in chunks no larger than the size of the output buffer.

The process used to move data from the intermediate buffer to the output buffer is according to the I/O mode selection.

8.3.1. PIO - Programmed I/O

This mode involves repetitive register accesses. In this mode the driver will write data to the output buffer one value at a time. As needed, the driver will repeatedly sleep for one system time tick in order to wait for additional space in the output buffer. This process is repeated until the data is exhausted or the I/O timeout expires, whichever occurs first.

8.3.2. BMDMA - Block Mode DMA

For DMA transfers, hardware onboard the 20AOF16C500KR is used to transfer the data without processor intervention. In this mode the driver checks for available space in the output buffer. Depending on the size of the write request, the driver may break the request into smaller transfers in order to ensure data integrity. When sufficient space is available a DMA transfer is performed. The volume of data moved in a single request is based upon the amount of data remaining in the request and the amount of space available in the buffer. If the remaining request will fit within the available space, then the data is transferred. Otherwise, if the threshold flag is set, then the driver will wait one timer tick before trying again. If the threshold flag is clear, then the driver will transfer up to the volume of data that can fill the buffer's space that exceeds the threshold level. The process is repeated until the data is exhausted or the I/O timeout expires, whichever occurs first.

8.3.3. DMDMA - Demand Mode DMA

In Demand Mode DMA, data is moved from the intermediate buffer to the output buffer in a single DMA transfer that occurs over time as the data appears in the output buffer. The process is repeated until the data is exhausted or the I/O timeout expires, whichever occurs first.

9. Sample Applications

The driver archive includes a variety of sample and test applications. While they are provided without support and without any external documentation, any problems reported will be addressed as time permits. The applications are command line based and produce text output for display on a console. All of the applications are built via the Overall Make Script (section 2.7, page 13), but each may be built individually by changing to its respective directory and issuing the commands “make clean” and “make all”. The initial output from each application includes information on its supported command line arguments. The following gives a brief overview of each application.

9.1. aout - Analog Output - .../aout/

This application outputs a repeating pattern on the first four output channels. The pattern is different for each channel, though they are synchronized at the same modest rate.

9.2. din - Digital Input - .../din/

This application reads the cable’s digital I/O signals and reports the values read to the console.

9.3. dout - Digital Output - .../dout/

This application writes a pattern to the cable’s digital output lines as it is displayed to the console.

9.4. fsamp - Sample Rate - .../fsamp/

This application reports the device configuration required to produce a user specified sample rate.

9.5. id - Identify Board - .../id/

This application reports detailed board identification information. This can be used with tech support to help identify as much technical information about the board as possible from software.

9.6. irq – Interrupt Test - .../irq/

This application performs complete testing to verify the operation of the board’s firmware interrupts.

9.7. led – LED Exerciser - .../led/

This application exercises the front panel LED.

9.8. regs - Register Access - .../regs/

This application provides menu based interactive access to the board’s registers, and reports other pertinent information to the console.

9.9. signals - Digital Signals - .../signals/

This application configures the board to drive the digital output signals for a user specified period of time. This is done to facilitate setup of test equipment to capture those signals during actual use.

9.10. txrate – Transmit Rate - `.../txrate/`

This application configures the board for its highest output sample rate then writes output as fast as possible. The purpose is to measure the peak sustainable output rate for the host, per the provided command line arguments.

Document History

Revision	Description
April 21, 2023	Updated to version 2.6.102.45.1.
March 9, 2023	Updated to version 2.6.102.45.0. Updated the kernel support table.
January 12, 2023	Updated to version 2.5.101.44.0. Updated the kernel support table. Added section on environment variables. Updated the information for the open and close calls. Minor editorial modifications.
March 2, 2022	Updated to version 2.4.97.38.0. Expanded automatic startup information. Updated the kernel support table. Minor editorial changes.
March 1, 2021	Updated to version 2.3.93.36.0. Updated the kernel support table. Minor editorial changes. Expanded automatic startup information.
September 17, 2019	Updated to version 2.2.87.28.0. Updated the kernel support table. Updated the inside cover page. Updated the CPU and kernel support section. Minor editorial changes. Updated Block Mode DMA macro and associated information. Document reorganization. Added a licensing subsection. Added WAIT_EVENT note. Renamed the GSC_WAIT_IO_* macros to AOF16C500KR_WAIT_IO_*. Document reorganization.
December 6, 2016	Updated to version 2.1.68.18.0. Removed the <code>built</code> field from the <code>/proc</code> file. Updated the kernel support table. Updated the command line arguments for the <code>din</code> , <code>fsamp</code> and <code>signals</code> sample applications. Removed all references to the <code>sbtest</code> sample application as it was never developed. Removed the non-inclusion disclaimer about the <code>signals</code> sample application. Updated the usage of the Wait Event <code>timeout_ms</code> field. Updated material on the open call. Added open access mode descriptions. Added support for infinite I/O timeouts. Updated the operating information section. Made various miscellaneous updates. Some document reorganization.
September 10, 2015	Updated to version 2.0.60.8.0. Updated the device node name to include a period before the device index. Removed double underscore that prefaced various data types.
March 3, 2014	Updated to version 1.4.52.0. Updated the kernel support data.
January 8, 2014	Updated to version 1.3.51.0. Updated the kernel support data.
November 15, 2013	Updated to version 1.3.50.0.
July 17, 2013	Updated to version 1.3.45.0. Updated the kernel support data.
July 20, 2012	Updated to version 1.3.39.0. Updated the kernel support data.
November 16, 2011	Updated to version 1.2.32.0.
July 18, 2011	Updated to version 1.1.27.0.
July 18, 2011	Initial release.